

ARMOURPLAN PVC MEMBRANE CLEANER

PRODUCT INFORMATION

A solvent based solution

Used to achieve satisfactory hot air weld between Armourplan membranes contaminated by moisture, building site dust and dirt

Also used as a general cleaner to remove dirt or wet adhesive.

Description	Solvent Cleaner
Tin Size	5 Litre
Colour	Clear
Product Number	05501485

FEATURES & BENEFITS

- Effective membrane weld preparation.
- Cost effective application.



PVC MEMBRANE CLEANER USE

Wash / scrub the area of membrane where Armourplan PVC Cleaner is to be applied with warm soapy water
Allow to dry

Apply Armourplan PVC Cleaner to membrane using a clean lint free cloth wearing appropriate PPE in accordance with the MSDS

Allow Armourplan PVC Cleaner to fully evaporate prior to welding

If the membrane becomes wet or soiled after the preparation the cleaning regime is to be repeated

Ensure that the cap is firmly placed on the container when not in use.



STORAGE

Store in a sealed container in dry conditions at a temperature between 5°C and 25°C. Shelf life 12 months in an unopened container, stored at the above temperature.

TYPICAL PROPERTIES

Description	Armourplan PVC membrane Cleaner
Base	Hydrocarbon Solvent
Solid Content	N/A
Viscosity	Non - Viscous
Colour	Colourless
Tack Life	Approx. 5 minutes
Coverage Rate	20 m ² /litre
Flash Point	-35 Deg C (PMCC)
Shelf Life	12 months

FURTHER PRODUCT INFORMATION

Full product literature, health & safety and technical sheets are available as downloads from our website

www.ikopolymeric.com or on request by email polymeric.marketing@iko.com.