

## ARMOURPLAN SC

### PRODUCT INFORMATION

Single coated PVC membrane for temporary roofing applications

Ideal for use as a waterproofing membrane on modular buildings as protection during storage and installation

Also used on garden house roofs and carports.

Either mechanically fixed using suitable IKOfix fastenings or adhered using Armourplan SC adhesive.

Overlaps are heat welded using suitable hot-air welding equipment

Supplied in pre-fabricated sheets, either factory hot air welded or in 50m long rolls.

### FEATURES & BENEFITS

- Good UV resistance and durability.
- Good mechanical properties and product performance.
- Efficient and safe installation.
- Secure seam welding quality.
- Aesthetically pleasing finish.
- 10 year product warranty.

Description	Single coated PVC membrane
Thickness	0.7mm
Width	2.12m / 1.5m
Length	50m
Colour	Mid grey (nearest RAL 7046)
Material	PVC
Reinforcement	Polyester
Product Number	58521206
Description	Single coated PVC membrane

### TYPICAL PROPERTIES

Property	Test Method	Unit	Result (min)
Thickness	EN 1849-2	mm	0.7
Weight	EN 1849-2	g/m <sup>2</sup>	900
Tensile strength	EN 12311-2	N/50mm	900 (MD) / 800 (TD)
Elongation at break	EN 12311-2	%	20 (MD) / 20 (TD)
Tear strength	EN 12310-2	N	180
Dimensional stability 6hrs at 80°C	EN 1107-2	%	<0.5 (MD) / <0.5 (TD)

### FURTHER PRODUCT INFORMATION

Full product literature, health & safety and technical sheets are available as downloads from our website

[www.ikopolymeric.com](http://www.ikopolymeric.com) or on request by email [polymeric.marketing@iko.com](mailto:polymeric.marketing@iko.com).