

## IKOfix ALUMINIUM CLAMPING STRIP

### PRODUCT INFORMATION

Used for securing the Armourplan or Spectraplan membrane at the top of an adhered upstand. Designed to clamp the membrane into. Allows for a bead of sealant to be applied to the upper edge to maintain a watertight termination against the substrate.

Description	Upstand Termination Restraint
Material	Aluminium
Length	2500mm
Depth	50mm
Thickness	2mm
Hole Diameter	5mm
Product Number	05493081



### FEATURES & BENEFITS

- Cold Application
- Quick and easy installation
- Cost effective application



### INSTALLATION

Position the Aluminium Clamping Strip at the top of the completed adhered upstand. Using suitable IKOfix fasteners secure into position at 250mm centres. Allow a 5mm gap between lengths of clamping strip. Apply the appropriate IKO Polymeric sealant. Bond and Seal sealant for the Spectraplan system or Armourplan PVC Sealant for the Armourplan system.

### TECHNICAL SPECIFICATION

Material	Aluminium
Length	2500mm
Gauge	2mm
Gauge Tolerance	±0.07mm
Length Tolerance	±3.0mm
General Tolerance	±0.4mm



### STORAGE

IKOfix Aluminium Clamping Strips should be kept dry. They should be stored raised off the surface of the roof and covered with a suitable waterproof layer

### FURTHER PRODUCT INFORMATION

Full product literature, health & safety and technical sheets are available as downloads from our website [www.ikopolymeric.com](http://www.ikopolymeric.com) or on request by email [polymeric.marketing@iko.com](mailto:polymeric.marketing@iko.com).