

IKOfix MEMBRANE PRESSURE PLATE (HS)

PRODUCT INFORMATION

Made of Aluzinc and ideal for use on rigid substrates such as cold roof build ups.

Used in conjunction with IKOfix fasteners for securing Armourplan SM/P or Spectraplan SM membranes in a layout as indicated by the project specific IKO Polymeric wind uplift calculation.

Description	Membrane Pressure Plate
Material	Aluzinc
Length	82mm
Width	40mm
Thickness	1mm
Hole Diameter	7mm
Product Number	37110700

FEATURES & BENEFITS

- Cold Application
- Excellent mechanical properties
- Quick and easy installation
- Cost effective application



INSTALLATION



1. Position the pressure plate and insert the fixing.
2. Using a drill fitted with the correct drive bar and stop bit screw the fastener into the substrate until the fixing depth is reached.

DESIGN PERFORMANCE INFORMATION

Membrane Pressure Plate (HS)		IKOfix Universal Fixing (0.7mm Steel Deck)	IKOfix Universal Fixing (Timber Deck)	IKOfix Concrete Fixing
Characteristic Resistance	N	1310	1310	1310

STORAGE

IKOfix Fasteners should be kept dry. They should be stored in their original cartons raised off the surface of the roof and covered with a suitable waterproof layer.

FURTHER PRODUCT INFORMATION

Full product literature, health & safety and technical sheets are available as downloads from our website www.ikopolymeric.com or on request by email polymeric.marketing@iko.com.