

SPECTRAPLAN D MEMBRANE

PRODUCT INFORMATION

Non-reinforced TPE membrane for detailing on Spectraplan roof systems

Offers excellent flexibility allowing the material to be formed easily into intricate details ensuring the roof installation is fully waterproofed

Adhered to suitable substrates using Spectraplan TPE Contact Adhesive

All overlaps and joints are heat welded using suitable hot-air welding equipment.

Used to form complex details such as pipe penetrations or external corners

Can be used to waterproof the joints between Spectraplan membrane coated metal flashing sections and gutter joints

FEATURES & BENEFITS

- Excellent flexibility for complex detailing
- Excellent UV resistance and durability
- Excellent mechanical properties and product performance
- Efficient and safe installation
- Secure seam welding quality

Description	Silicone Sealant
Thickness	1.5mm
Length	10m, 25m
Width	0.75m
Colour	Light Grey
Material	TPE
Reinforcement	None



SPECTRAPLAN D MEMBRANE ROLL SIZES

Colour	Width	Length	Item Number
Light Grey	0.75m	10m	44440008
Light Grey	0.75m	25m	44440005

FURTHER PRODUCT INFORMATION

Full product literature, health & safety and technical sheets are available as downloads from our website www.ikopolymeric.com or on request by email polymeric.marketing@iko.com